# **CLS44**0

## Column Speaker

# **AUDAC**

#### Features

- Slim line ALU design
- Clear and crisp sound reproduction
- Mounting bracked included
- -8 x 3" drivers
- Different power taps
- Aluminium front finish

### Applications

- Auditoria
- Houses of worship
- Sports facilities
- Conference facilities
- Public buildings
- Meeting rooms



The CLS440 features a speaker unit consisting of 8 x 3" drivers, capable of producing a power up to 40 Watt RMS.

The advanced technology gives the effect of listening to a single sound source, with the same dimensions of the total speaker unit. This guarantees a wide sound dispersion and improved speech intelligibility in acoustically difficult venues.

Some typical applications of column speakers are: houses of worship, auditoria, sports facilities, conference facilities, meeting rooms, public buildings, educational facilities, ...

It is fitted with a 100V line transformer with power taps for 40W and 20W.

The speaker housing is made of sturdy aluminium coated in a white color, offering a timeless design which will be appreciated in any interior.

For the mounting of the CLS440, a special bracket is included, which makes it possible to focus the speaker.



### **▶** Specifications

SYSTEM SPECIFICATIONS	
Max. power	60 W
RMS power	40 W
Line voltage	100 V
Power taps	40W / 250 Ohm
	20W / 500 Ohm
Frequency response -3dB	170 Hz - 15 kHz
Sound pressure W/1m	92 ± 3 dB
PRODUCT FEATURES	
Dimensions (Width x Height x Diameter)	834 x 104 x 86 mm
Weight net	3.5 Kg
Drivers	8 x 3"
Construction	Aluminium
Front finish	Aluminium grill
Colour	White (RAL 9010)
SHIPPING & ORDERING	
Packaging	Carton box
Shipping weight & volume	

\*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products